

FLOOR SEAL



Classic SealTM

BASE COAT FLOOR SEAL

PRODUCT SPECIFICATION BULLETIN

THE FINEST IN JANITORIAL PRODUCTS, SUPPLIES AND EQUIPMENT SINCE 1946

Product No. 123

PRODUCT DESCRIPTION

Date revised 9/2004

LAWTON'S CLASSIC SEAL is a water based, low odor resilient floor sealer with the added exceptional features of easy removability and high initial gloss. LAWTON'S CLASSIC SEAL penetrates, locks on and fills surface pores leaving a superior bonding surface for a floor finish.

DIRECTIONS

FLOOR PREPARATION: Strip floors with LAWTON'S BLAST OFF to remove all soils, seals and finishes. Vacuum up. Flood rinse with neutralizer conditioner. Vacuum up. Using a clean mop, damp mop floor with clean water. Let dry a minimum of 60 minutes.

APPLICATION: Apply LAWTON'S CLASSIC SEAL with a clean synthetic mop to a clean, dry floor. Under normal conditions, apply up to three coats allowing 60 minutes between coats.

MAINTENANCE: Dust mop daily with treated dust mop. Mop or scrub as needed with LAWTON'S NLC.

RECOAT: Scrub floor with green or blue scrub pad and LAWTON'S NLC. Rinse and let dry. Apply 1 or 2 coats of LAWTON'S quality floor finish.

CAUTIONS

CAUTION: Keep out of reach of children. Any liquids spilled on a finished floor will cause a hazardous, slippery condition. Clean up of spills should have immediate attention. Avoid eye contact. For eye contact, rinse with water. If irritation persists, get medical help. Do not swallow. If swallowed get medical help immediately.

WARNING: Do not pour unused finish back into container as it will damage the product.

CAUCIÓN: Mantenga fuera del alcance de los niños. Cualquier líquido derramado en un piso acabado causará una condición peligrosa deslizada. Cualquier derramamiento debe recibir atención inmediata. Evite el contacto con los ojos. En caso de que hay contacto con los ojos, enjuague inmediatamente con agua. Si persiste la irritación, busque asistencia médica. Este producto no es para beber. Si se traga, busque asistencia médica inmediatamente.

AVISO: No vacie el restante del acabado nuevamente dentro del envase pues dañará el producto.

HAZARDOUS INGREDIENTS:

Dipropylene glycol monomethylether..... CAS NO. 34590-94-8

2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate..... CAS NO. 25265-77-4

Tributoxyethylphosphate..... CAS NO. 78-51-3

PROTECTIVE EQUIPMENT

It is recommended to wear protective gloves and protective eyewear when using this or any chemical cleaning product.

TECHNICAL DATA

Nonvolatile solids.....	16.7 ± 1% by wt.
Color and appearance.....	Milk white liquid.
Odor.....	Mild ammonia odor.
Viscosity.....	Water thin.
pH.....	9.0 ± .5 @ 25°C.
Specific Gravity.....	1.020 @ 25°C.
Weight per gallon.....	8.48 lbs. per gallon.
Dry time, (thin coat) standard humidity.....	10 min.
Dry time (average coat).....	15-20 min.
Cure time to re-coat (thin coat).....	30 min.
Cure time to re-coat (average coat).....	30-60 min.
Leveling.....	Excellent.
Gloss.....	Good.
Black heel mark resistance.....	Good.
Detergent resistance.....	Excellent.
Removability.....	Excellent with high-end strippers.
Slip resistance.....	Passes standard.
Nonyellowing.....	Good.
Dry film clarity.....	Excellent.
Freeze / thaw stability.....	Passes standard.
V.O.C. (Volatile Organic Content).....	5.4% by wt.
Flash point.....	Nonflammable.
Shelf life (stored properly).....	1 year.

READY TO USE

LAWTON BROS., INC. MANUFACTURING CHEMISTS

ORLANDO

2515 DINNEEN AVENUE
P.O. BOX 547635
ORLANDO, FL 32854-7635
PH: 407-291-2501 ● 800-432-0813
FAX: 407-290-0471

CLEARWATER BRANCH

14420 - 60TH STREET NORTH
CLEARWATER, FL 33760
PH: 727-531-1179 ● 800-328-3210
FAX: 727-531-4566

OCALA BRANCH

1507 SOUTH PINE AVENUE
OCALA, FL 34474
PH: 352-629-8810 ● 800-421-5777
FAX: 352-629-3797

MELBOURNE BRANCH

114 SOUTH BABCOCK STREET
MELBOURNE, FL 32901
PH: 321-951-0861
FAX: 321-951-9210