

MATERIAL SAFETY DATA SHEET

M.S.D.S. Prepared to comply with O.S.H.A. Hazard Communication Standard, 29 CFR 1910.1200

HAZARD RATING 0 = Insignificant 1 = Slight 2 = Moderate

3 = High 4 = Extreme Health Fire Reactivity

Prod No.: .217373 Date Prepared: 10/2010 PROD NAME: EXTREME COATING REMOVER SECTION I: MANUFACTURER'S INFORMATION Manufactured By: LAWTON BROS., INC. **EMERGENCY PHONE NO.: INFOTRAC 1-800-535-5053** Street Address: 2515 Dinneen Ave. Information Phone No.: 1-407-291-2501 Mailing Address: P.O. Box 547635 Product Type: COATING STRIPPER Formula Type: EMULSIFIABLE SOLVENT BLEND City/State/Zip Orlando, FL. 32854-7635

SECTION IIA: HAZARDOUS INGREDIENT INFORMATION

HAZARDOUS COMPONENTS	C.A.S. REG NOS.	OSHA PEL	ACGIH TLV	WT.% MAX		
ETHYLENEGLYCOLMONOBUTYLETHER	111-76-2	50 ppm	25 ppm	5.00		

HAZARDOUS COMPONENTS LISTED ARE SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III AND 40 CFR PART 372.

SECTION IIB: NON-HAZARDOUS INGREDIENT GENERAL INFORMATION

NON-HAZARDOUS COMPONENTS	C.A.S. REG NOS.	OSHA PEL	ACGIH TLV	WT.% MAX
BENZYL ALCOHOL	100-51-6	NOT AVAIL	NOT AVAIL	70.00
NON-IONIC DETERGENT BLEND	NON-HAZARDOUS MIXTURE			
INERT THICKENER				

SECTION III: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: >212°F	Evaporation Rate vs H₂O:	SLOWER	Viscosity:	THICK LIQUID	Specific Gravity:	1.094
Freezing Point: < 32°F	Vapor Density vs Air:	NA	Sol. in H₂O:	DISPERSIBLE	pH @ 25ºC:	NEUTRAL

Appearance and odor: COLORLESS TO LIGHT AMBER, THICKENED LIQUID WITH MILD SOLVENT ODOR.

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (method used): 199°F TCC Flammable Limits UEL LEL

Extinguishing Media: CO2, FOAM AND DRY CHEMICAL.

Special Fire Fighting Procedure: SCBA RECOMMENDED; SMOTHER TO EXCLUDE AIR. DO NOT USE WATER. HANDLE AS AN OIL

FIRE CLASS B FIRE PROCEDURES

Unusual Fire & Explosion Hazards: COMBUSTIBLE LIQUID. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

SECTION V: REACTIVITY DATA

Stability: STABLE Incompatibility: DO NOT MIX WITH ANY OTHER CHEMICALS NOT RECOMMENDED ON LABEL. Hazardous Decomposition Products (thermal): OXIDES OF CARBON.

SECTION VI: HEALTH HAZARDS, SIGNS OF OVEREXPOSURE OR ACCIDENTAL CONTACT

Eyes: WILL CAUSE CORNEA DAMAGE. REDNESS AND SHARP EYE PAIN ARE SYMPTOMATIC.

Skin: WILL CAUSE IRRITATION.

Inhalation: OVEREXPOSURE CAN CAUSE LIVER AND KIDNEY INJURY. DIZZINESS, HEADACHE AND NAUSEA MAY BE SYMPTOMATIC.

Swallowing: ULCERATION TO INTERNAL BODY TISSUE. SEVERE STOMACH PAIN, DIZZINESS, HEADACHE AND NAUSEA MAY

BE SYMPTOMATIC.

Carcinogenicity: THIS PRODUCT IS NOT A SUSPECTED CARCINOGEN BASED ON COMPONENT DATA.

SECTION VII: EMERGENCY FIRST AID PROCEDURES

Eyes: FLUSH WITH COOL WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL HELP.

Skin: RINSE WITH WATER.

Inhalation: FOR OVEREXPOSURE, REMOVE FROM AFFECTED AREA. IF SYMPTOMS PERSIST, GET MEDICAL HELP.

Swallowing: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL HELP.

SECTION VIII: PERSONAL PROTECTION INFORMATION

Protective Equipment: IT IS RECOMMENDED TO WEAR RUBBER GLOVES AND PROTECTIVE EYEWEAR WHEN USING THIS OR ANY CHEMICAL CLEANING PRODUCT. IF SPRAY APPLYING, VENTILATION AND BREATHING PROTECTION IS RECOMMENDED.

SECTION IX: SPILL OR LEAK PROCEDURES

If Spilled or Released: MOP UP OR USE ABSORBENT SWEEPING COMPOUND. PROPERLY CONTAIN WASTE Waste Disposal Method: DISPOSAL SHOULD BE IN ACCORDANCE WITH STATE AND FEDERAL WASTE DISPOSAL LAWS.

SECTION X: STORAGE AND HANDLING INFORMATION

STORE IN ORIGINAL CLOSED CONTAINER IN COOL AREA. KEEP OUT OF REACH OF CHILDREN.

SECTION XI: D.O.T. HAZARD CLASS AND SHIPPING NAME

Hazard Class: NONE

Proper Shipping Name: NOT REGULATED.