

HEAVY DUTY COATING REMOVER



EXTREMETM **COATING REMOVER** FLOOR COATING REMOVER SAFE FOR USE ON VCT FLOOR TILE REMOVES HARD TO STRIP URETHANES AND ACRYLICS

PRODUCT SPECIFICATION BULLETIN

THE FINEST IN JANITORIAL PRODUCTS, SUPPLIES AND EQUIPMENT SINCE 1946

Product No. .217373

PRODUCT DESCRIPTION

Date: 3/2011

LAWTON'S EXTREME COATING REMOVER is a powerful 100% active, low odor, neutral pH floor coating remover. It's designed to safely and quickly remove heavy buildup finishes, hard to remove seals, semi-permanent urethane and acrylic finishes from hard floors, VCT and some other resilient flooring (see pre-test). For best results, apply when floor temperature is above 60°F.

DIRECTIONS

DIRECTIONS AND CAUTIONS: Place safety signs. When applying product, the floor will become slippery. Take care not to splash on walls, painted baseboards or other unwanted areas. Work in well ventilated area. Do not use on asphalt tile, linoleum or rubber floors.

PRE-TEST on an inconspicuous area of the floor. Apply stripping solution to small test area and allow to stand 20 minutes. Wipe off with towel, rinse and examine floor for bleeding or softening. Do not continue use of product if any bleeding or softening is observed.

APPLICATION DIRECTIONS: **LAWTON'S EXTREME COATING REMOVER** is ready to use. No dilution is necessary.

- ⇒ **SHAKE WELL** the thickened concentrate and pour directly onto the immediate work area. Spread evenly completely covering the surface. Work in easily manageable areas. Allow the product to work until the coating is wrinkled or dissolved through to the floor. Urethane coatings will usually wrinkle and acrylic coatings will soften or dissolve as the stripper is applied.
- ⇒ Once the coating is wrinkled or softened, apply a dilute solution of **LAWTON'S BLAST OFF** and scrub.
- ⇒ Pick up the exhausted solution. Flood rinse and vacuum up rinse water. Inspect floor to see if a second application is necessary.

CAUTIONS

CAUTION: Do not swallow. If swallowed, get medical help immediately. Do not get in eyes. If eyes are contacted by product, rinse thoroughly with cool water. If cleaning by hand for an extended period, it is recommended to wear rubber gloves to protect skin from irritation. KEEP OUT OF REACH OF CHILDREN. Combustible liquid. Keep away from heat, sparks and open flame.

CUIDADO: Este producto no es para beber. Si se traga, busque asistencia médica inmediatamente. Evite contacto con los ojos. Si hace contacto con sus ojos, enjuáguelos con agua fresca. Si limpia a mano, es recomendado que use guantes de goma para proteger su piel contra la irritación. SIEMPRE MANTENGA ESTE PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS. Líquido combustible. Guarde lejos de calor, de chispas y de la llama abierta.

HAZARDOUS INGREDIENTS:

Ethylene glycol monobutyl ether CAS NO. 111-76-2

PROTECTIVE EQUIPMENT

It is recommended to wear protective gloves and protective eyewear when using this or any chemical cleaning product. When spray applying, ventilation and breathing protection is recommended.

TECHNICAL DATA

Total active ingredients 100% by wt.
Nonvolatile matter 12% by wt.
Color & appearance Translucent colorless liquid.
Odor Mild solvent odor.
Viscosity Thickened Liquid.
pH Neutral.
Specific Gravity 1.061 @ 25°C.
Weight per gallon 8.82 lbs. Per gallon.
Biodegradable (organic components) Yes.
Phosphorus content None.
Detergent type Nonionic.
Foam height None.
VOC (Volatile Organic Content) 88% by wt.
Flash point 199° F.
Shelf life (stored properly) 2 years.

READY TO USE

LAWTON BROS., INC. MANUFACTURING CHEMISTS

ORLANDO

2515 DINNEEN AVENUE
P.O. BOX 547635
ORLANDO, FL 32854-7635
PH: 407-291-2501 ● 800-432-0813
FAX: 407-290-0471

CLEARWATER BRANCH

14420 - 60TH STREET NORTH
CLEARWATER, FL 33760
PH: 727-531-1179 ● 800-328-3210
FAX: 727-531-4566

OCALA BRANCH

1507 SOUTH PINE AVENUE
OCALA, FL 34474
PH: 352-629-8810 ● 800-421-5777
FAX: 352-629-3797

MELBOURNE BRANCH

114 SOUTH BABCOCK STREET
MELBOURNE, FL 32901
PH: 321-951-0861
FAX: 321-951-9210