

SECTION IX: SPILL OR LEAK PROCEDURES

Proper Shipping Name: ORM-D

SECTION X: STORAGE AND HANDLING INFORMATION

SECTION XI: D.O.T. HAZARD CLASS AND SHIPPING NAME
Hazard Class: COMBUSTIBLE LIQUID

STORE IN ORIGINAL CLOSED CONTAINER IN COOL AREA. KEEP OUT OF REACH OF CHILDREN.

MATERIAL SAFETY DATA SHEET

M.S.D.S. Prepared to comply with O.S.H.A. Hazard Communication Standard, 29 CFR 1910.1200 HAZARD RATING
0 = Insignificant
1 = Slight
2 = Moderate

Health 2 Fire 2 Reactivity 0

3 = High 4 = Extreme

| PROD NAME: MINERAL SPIRITS | | | | Prod No.: 490 | | Date Revised: 7/2004 | |
|--|----------------|---------------|-----------------|--|------------------|----------------------|----------|
| SECTION I: MANUFACTURER'S INFORMATION | | | | | | | |
| Manufactured By: LAWTON BROS., INC. | | | | EMERGENCY PHONE NO.: INFOTRAC 1-800-535-5053 | | | |
| Street Address: 2515 Dinneen Ave. | | | | Information Phone No.: 1-407-291-2501 | | | |
| Mailing Address: P.O. Box 547635 | | | | Product Type: SOLVENT & CLEANER | | | |
| City/State/Zip Orlando, FL. 32854-7635 | | | | Formula Type: ALIPHATIC HYDROCARBONS | | | |
| SECTION II: HAZARDOUS INGREDIENT INFORMATION | | | | | | | |
| HAZARDOUS COMPONENTS | | | C.A.S. REG NOS. | | OSHA PEL | ACGIH TLV | WT.% MAX |
| ALIPHATIC HYDROCARBON SOLVENTS | | | 64741-65-7 | | 100 ppm | 100 ppm | 100.00 |
| | | | | | | | |
| | | | | | | | |
| HAZARDOUS COMPONENTS LISTED ARE SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III AND 40 CFR PART 372. | | | | | | | 372 |
| SECTION III: PHYSICAL AND CHEMICAL PROPERTIES | | | | | | | |
| Boiling Point: | 355°F | Evaporation | | | WATER THIN | Specific | .780 |
| INITIAL | | Rate BuAc=1: | | | | Gravity: | |
| Freezing Point: | NA | Vapor Density | 5.3 | Solubility in | IMMISCIBLE | pH @ 25ºC: | NA |
| Annaa | ronce and adam | Air=1: | | H ₂ O: | (ODODI ESS CI | DADE MINEDAL CE | NDITC\ |
| Appearance and odor: WATER CLEAR LIQUID WITH MILD SOLVENT ODOR (ODORLESS GRADE MINERAL SPIRITS) SECTION IV: FIRE AND EXPLOSION HAZARD DATA | | | | | | | |
| | | | HAZAKU DAI | A | E | | |
| Flash Point (method used): 125°F TCC | | | | | Flammable Limits | LEL 1 | UEL 7 |
| Extinguishing Media: COMBUSTIBLE LIQUID, USE WATER FOG, FOAM, CO ₂ , OR DRY CHEMICAL. Special Fire Fighting Procedure: DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR, INCLUDING A POSITIVE | | | | | | | |
| PRESSURE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED | | | | | | | |
| CONTAINERS WITH WATER. | | | | | | | |
| Unusual Fire & Explosion Hazards: COMBUSTIBLE LIQUID. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. SECTION V: REACTIVITY DATA | | | | | | | |
| | | | | | | | |
| Stability: STABLE Incompatibility: DO NOT MIX WITH ANY OTHER CHEMICALS NOT RECOMMENDED ON LABEL. Hazardous Decomposition Products (thermal): ORGANIC ACIDS AND OXIDES OF CARBON. | | | | | | | |
| SECTION VI: HEALTH HAZARDS, SIGNS OF OVEREXPOSURE OR ACCIDENTAL CONTACT | | | | | | | |
| Eves: IRRITANT. | | | | | | | |
| Skin: IRRITANT. REPEATED CONTACT MAY CAUSE DERMATITIS. | | | | | | | |
| Inhalation: OVEREXPOSURE CAN CAUSE LIVER AND KIDNEY INJURY. DIZZINESS, HEADACHE AND NAUSEA MAY BE | | | | | | | |
| SYMPTOMATIC. | | | | | | | |
| Swallowing: STOMACH PAIN, DIZZINESS, HEADACHE AND NAUSEA MAY BE SYMPTOMATIC. MAY RESULT IN CENTRAL NERVOUS SYSTEM DEPRESSION. IF VOMITING, ASPIRATION INTO THE LUNGS MAY RESULT IN ASPIRATION | | | | | | | |
| PNEUMONITIS. | | | | | | | |
| Carcinogenicity: THIS PRODUCT IS NOT A SUSPECTED CARCINOGEN BASED ON COMPONENT DATA. | | | | | | | |
| SECTION VII: EMERGENCY FIRST AID PROCEDURES | | | | | | | |
| Eyes: FLUSH WITH COOL WATER FOR 15 MINUTES. GET IMMEDIATE MEDICAL HELP. | | | | | | | |
| Skin: WASH WITH SOAP AND WATER. | | | | | | | |
| Inhalation: FOR OVEREXPOSURE, REMOVE FROM AFFECTED AREA. IF SYMPTOMS PERSIST, GET MEDICAL HELP. Swallowing: DO NOT INDUCE VOMITING. GET <i>IMMEDIATE</i> MEDICAL HELP. | | | | | | | |
| | | | | | | | |
| SECTION VIII: PERSONAL PROTECTION INFORMATION | | | | | | | |
| Protective Equipment: IT IS RECOMMENDED TO WEAR RUBBER GLOVES AND PROTECTIVE EYEWEAR WHEN USING THIS OR ANY CHEMICAL CLEANING PRODUCT. IF SPRAY APPLYING, VENTILATION AND BREATHING PROTECTION IS RECOMMENDED. | | | | | | | |
| CECTION IV. CDU LOD LEAK DECCEPTION. | | | | | | | |

If Spilled or Released: MOP UP OR USE ABSORBENT SWEEPING COMPOUND. PROPERLY CONTAIN WASTE.
Waste Disposal Method: DISPOSAL SHOULD BE IN ACCORDANCE WITH STATE AND FEDERAL WASTE DISPOSAL LAWS.