

BLACK PIGMENTED FLOOR FINISH



POSTALTM BLACK WAX

**DURABLE • HIGH GLOSS
HIGH SPEED BURNISH
THERMOPLASTIC FLOOR FINISH**

PRODUCT SPECIFICATION BULLETIN

THE FINEST IN JANITORIAL PRODUCTS, SUPPLIES AND EQUIPMENT SINCE 1946

Product No. 108BLK

PRODUCT DESCRIPTION

Date prepared 6/2007

LAWTON'S POSTAL BLACK WAX is a black pigmented, durable, high gloss floor finish designed to renew the color and gloss of older flooring. A versatile easy to apply floor finish that holds up to heavy traffic, detergent scrubbing and ultra-high speed burnishing. **POSTAL BLACK WAX** is the ideal choice for low maintenance programs as well.

DIRECTIONS

FLOOR PREPARATION: Remove old seals and finishes with LAWTON'S BLAST OFF – use as directed. Rinse floor well with clean water and allow to thoroughly dry. Seal floor with LAWTON'S CLASSIC SEAL (optional). Apply 1 or 2 coats of seal as directed.

WARNING: Exercise caution when applying a color pigmented floor coating not to splash base boards or unwanted areas.

APPLICATION: Apply 2 to 4 coats of **LAWTON'S POSTAL BLACK WAX**, using a clean finish mop, allowing 30 to 60 minutes dry time between coats. For best results, apply thin even coats with 30 minutes dry time between coats.

MAINTENANCE: (1) Dust mop daily with treated dust mop. (2) Damp mop or auto mop daily with LAWTON'S SURPASS or LAWTON'S N-L-C. (3) Burnish with LAWTON'S UHS floor pad on a 1500-3000 rpm burnisher. (4) As needed, apply LAWTON'S SURPASS and burnish using mop on method as directed.

FUTURE CARE: When burnishing no longer restores gloss, scrub floor with LAWTON'S N-L-C, rinse thoroughly and apply 2 coats of **POSTAL BLACK WAX**.

CAUTIONS

CAUTION: Keep out of reach of children. Any liquids spilled on a finished floor will cause a hazardous, slippery condition. Clean up of spills should have immediate attention. Avoid eye contact. For eye contact, rinse with water. If irritation persists, get medical help. Do not swallow. If swallowed get medical help immediately.

WARNING: Do not pour unused finish back into container as it will damage the product.

CAUCIÓN: Mantenga fuera del alcance de los niños. Cualquier líquido derramado en un piso acabado causará una condición peligrosa deslizada. Cualquier derramamiento debe recibir atención inmediata. Evite el contacto con los ojos. En caso de que hay contacto con los ojos, enjuague inmediatamente con agua. Si persiste la irritación, busque asistencia médica. Este producto no es para beber. Si se traga, busque asistencia médica inmediatamente.

AVISO: No vacie el restante del acabado nuevamente dentro del envase pues dañará el producto.

HAZARDOUS INGREDIENTS:

Diethyleneglycolmonoethylether.....	CAS No. 111-90-0
Dipropyleneglycolmonomethylether	CAS No. 34590-94-8
2,2,4-Trimethyl-1,3-pentanediolmonoisobutyrate	CAS No. 25265-77-4
Tributoxyethylphosphate.....	CAS No. 78-51-3

PROTECTIVE EQUIPMENT

It is recommended to wear protective gloves and protective eyewear when using this or any chemical cleaning product. When spray applying, ventilation and breathing protection is recommended.

TECHNICAL DATA

Nonvolatile solids.....	20.0 ± 1% by wt.
Color and appearance.....	Milk black liquid.
Odor.....	Mild ammonia odor.
Viscosity.....	Water thin.
pH.....	9.0 ± .5 @ 25°C.
Specific Gravity.....	1.032 @ 25°C.
Weight per gallon.....	8.58 lbs. per gallon.
Dry time, (thin coat) standard humidity.....	10 min.
Dry time (average coat).....	15-20 min.
Cure time to re-coat (thin coat).....	30 min.
Cure time to re-coat (average coat).....	30-60 min.
Leveling.....	Excellent.
Gloss.....	Excellent.
Black heel mark resistance.....	Excellent.
Detergent resistance.....	Excellent.
Removability.....	Yes with good high-end strippers.
Slip resistance.....	Passes .5 on James machine.
Nonyellowing.....	Good.
Dry film clarity.....	Excellent.
Freeze / thaw stability.....	Passes standard.
V.O.C. (Volatile Organic Content).....	6.0% by wt.
Flash point.....	Nonflammable.
Shelf life (stored properly).....	>1 year.

READY TO USE

LAWTON BROS., INC. MANUFACTURING CHEMISTS

ORLANDO

2515 DINNEEN AVENUE
P.O. BOX 547635
ORLANDO, FL 32854-7635
PH: 407-291-2501 • 800-432-0813
FAX: 407-290-0471

CLEARWATER BRANCH

14420 - 60TH STREET NORTH
CLEARWATER, FL 33760
PH: 727-531-1179 • 800-328-3210
FAX: 727-531-4566

OCALA BRANCH

1507 SOUTH PINE AVENUE
OCALA, FL 34474
PH: 352-629-8810 • 800-421-5777
FAX: 352-629-3797

MELBOURNE BRANCH

114 SOUTH BABCOCK STREET
MELBOURNE, FL 32901
PH: 321-951-0861
FAX: 321-951-9210