

# HIGH SOLIDS FLOOR FINISH



# THIRTY 30<sup>TM</sup>

ULTRA HIGH SOLIDS  
EXTENDED WEAR FLOOR FINISH  
FOR RESILIENT AND HARD FLOORS

## PRODUCT SPECIFICATION BULLETIN

THE FINEST IN JANITORIAL PRODUCTS, SUPPLIES AND EQUIPMENT SINCE 1946

Product No. 107

### PRODUCT DESCRIPTION

Date 12/2006

**LAWTON'S THIRTY 30** is a durable, extended wear, high gloss floor finish built with ultra high solids to reduce application labor. The durable hardness characteristic of **LAWTON'S THIRTY 30** extends the useful life and appearance of your floor between maintenance operations. The ultra high solids saves you time and money by giving optimum appearance faster with a minimum of labor.

### DIRECTIONS

**FLOOR PREPARATION:** Remove old seals and finishes with LAWTON'S BLAST OFF. Rinse floor well with clean water and allow to thoroughly dry.

**APPLICATION: Cautions when applying:** Do not apply if floor temperature is below 60°F or when relative humidity is near 100%. Do not apply heavy coats. Do not use a standard string mop.

➔ **APPLY 1 to 3 THIN COATS** of **LAWTON'S THIRTY 30**, using a clean flat mop. Allow 30 to 60 minutes dry time between coats.

**MAINTENANCE:** (1) Dust mop daily with treated dust mop. (2) Damp mop or auto mop daily with LAWTON'S N-L-C. (3) Burnish with LAWTON'S UHS floor pad on a 1500-3000 rpm burnisher. (4) As needed, clean and restore the floor surface with LAWTON'S RESTORER. Using mop on method, apply one coat of LAWTON'S RESTORER. Let dry then burnish.

**FUTURE CARE:** When burnishing no longer restores gloss, scrub floor with LAWTON'S N-L-C, rinse thoroughly and apply 1 or 2 coats of **THIRTY 30** floor finish.

### CAUTIONS

**CAUTION:** Keep out of reach of children. Any liquids spilled on a finished floor will cause a hazardous, slippery condition. Clean up of spills should have immediate attention. Avoid eye contact. For eye contact, rinse with water. If irritation persists, get medical help. Do not swallow. If swallowed get medical help immediately.

**WARNING:** Do not pour unused finish back into container as it will damage the product.

**CAUCIÓN:** Mantenga fuera del alcance de los niños. Cualquier líquido derramado en un piso acabado causará una condición peligrosa deslizadiza. Cualquier derramamiento debe recibir atención inmediata. Evite el contacto con los ojos. En caso de que hay contacto con los ojos, enjuague inmediatamente con agua. Si persiste la irritación, busque asistencia médica. Este producto no es para beber. Si se traga, busque asistencia médica inmediatamente.

**AVISO:** No vacie el restante del acabado nuevamente dentro del envase pues dañará el producto.

### HAZARDOUS INGREDIENTS:

Diethyleneglycolmonoethylether ..... CAS NO. 111-90-0  
Tributoxyethylphosphate ..... CAS NO. 78-51-3

### PROTECTIVE EQUIPMENT

It is recommended to wear protective gloves and protective eyewear when using this or any chemical cleaning product.

### TECHNICAL DATA

Nonvolatile solids ..... 30 ± .5% by wt.  
Color and appearance ..... Milk white liquid.  
Odor ..... Mild ammonia odor.  
Viscosity ..... Water thin.  
pH ..... 9.0 ± .5 @ 25°C.  
Specific Gravity ..... 1.049 @ 25°C.  
Weight per gallon ..... 8.72 lbs. per gallon.  
Dry time ..... 30 min.  
Cure time to recoat ..... 30 to 60 min.  
Leveling ..... Excellent.  
Gloss ..... Excellent.  
Detergent resistance ..... Excellent.  
Removability ..... Good.  
Slip resistance ..... Passes standard.  
Nonyellowing ..... Good.  
Dry film clarity ..... Excellent.  
Freeze / thaw stability ..... Passes standard.  
Flash point ..... Nonflammable.  
Shelf life (stored properly) ..... 1 year.

## READY TO USE

### LAWTON BROS., INC. MANUFACTURING CHEMISTS

#### ORLANDO

2515 DINNEEN AVENUE  
P.O. BOX 547635  
ORLANDO, FL 32854-7635  
PH: 407-291-2501 • 800-432-0813  
FAX: 407-290-0471

#### CLEARWATER BRANCH

14420 - 60<sup>TH</sup> STREET NORTH  
CLEARWATER, FL 33760  
PH: 727-531-1179 • 800-328-3210  
FAX: 727-531-4566

#### OCALA BRANCH

1507 SOUTH PINE AVENUE  
OCALA, FL 34474  
PH: 352-629-8810 • 800-421-5777  
FAX: 352-629-3797

#### MELBOURNE BRANCH

114 SOUTH BABCOCK STREET  
MELBOURNE, FL 32901  
PH: 321-951-0861  
FAX: 321-951-9210